

617 to 960 MHz + 1710 to 2700 MHz Log Periodic Antenna, 10 to 11 dBi, Dual Band, High gain, Type N Female Connector, V-pol

**KP-LP1003**



**Features**

- Frequency coverage for 617 MHz to 2700 MHz
- Very High Gain 11 dBi Directional Antenna
- Each connector covers wide band of frequencies
- Easy Install universal mounting bracket provided
- Weatherproof ABS – UV Resistance PVC radome
- Pigtail – 12 inches
- N-Type Female connector

**Applications**

- Point-to-point, LPWAN, LoRA, LTE-M, NB-IoT, IoT, M2M applications
- 5G / 4G LTE B1 to B10, B12 to B20, B23, B24, B25, B28 / 3G / GSM / AWS / WLAN operation supported
- 5G Bands supported
- DAS (Distributed Antenna Systems)
- IEEE 802.11a / b / g / n / ac / ad / ah/ ax Wi-Fi applications
- Public safety, utilities, CCTV and local radio coverage
- Smart cities expansion for coverage and IOT / IIOT

**Description**

The KP-LP1003 from KP Performance Antennas is a high-performance log periodic antenna specifically designed to aesthetically pleasing design. The KP-LP1003 operate from 617 to 2700 MHz for point-to-point applications, 5G, LTE, CMDA, LoRA, IoT, WIFI, where directivity and coverage are very important. The KP Performance Antennas KP-LP1003 has 11 dBi of gain which is ideal for boosting.

The KP Performance Antennas KP-LP1003 has Vertical polarization, 75 horizontal beamwidth, and 50 vertical beamwidth for point-to-point communication. The included mounting brackets allow for either vertical or horizontal mounting configurations with easy install instructions. Where there is weak coverage and needs to reach further distances, log periodic antennas are best. The directional KP-LP1003 antenna has 1 Type N Female connector on a 12 Inches long pigtail.

KP Performance KP-LP1003 log periodic antenna operates in 5G bands n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n34, n38, n39, n40, n41, n53, n65, n66, n67, n67, n70, n71, n80, n81, n82, n83, n84, n85, n86, n89, n90, n91, n92, n93, n94, n95, n97, n98 with a 11 dBi max. This 617 to 2700 MHz 5G directional log periodic antenna with Type N connector is in stock and ready to ship the same day. Our expert technical support and friendly, knowledgeable customer service personnel are available to assist you with your particular needs for high performance Log Periodic antenna engineered for superior performance antennas.

**Configuration**

Design	Log Periodic
Band Type	Multi
Radiation Pattern	Directional
Polarization	Vertical
Cable Type	RG58/U
Cable Length	11.81 in [299.97 mm]
Connector Type	N Female
Number of Ports	1

**Electrical Specifications**

Description	Minimum	Typical	Maximum	Units
Frequency Range	617		2,700	MHz
Input VSWR		1.5:1	2:1	
Impedance		50		Ohms

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [617 to 960 MHz + 1710 to 2700 MHz Log Periodic Antenna, 10 to 11 dBi, Dual Band, High gain, Type N Female Connector, V-pol KP-LP1003](#)

617 to 960 MHz + 1710 to 2700 MHz Log Periodic Antenna, 10 to 11 dBi, Dual Band, High gain, Type N Female Connector, V-pol

**KP-LP1003**



Gain	10	11	dBi
Input Power		50	Watts

**Specifications by Band**

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	0.617 to 0.698	0.698 to 0.96	1.71 to 2.7			GHz
Gain	10	10	11			dBi
Horizontal HPBW	75	75	60			Degrees
Vertical HPBW	50	50	40			Degrees
Front to Back Ratio	18	18	20			dB
VSWR Max	2:1	2:1	1.5:1			
Maximum Input Power	50	50	50			Watts

**Mechanical Specifications**

Radome Material	ABS
<b>Size</b>	
Length	17.52 in [445.01 mm]
Width	8.07 in [204.98 mm]
Height	1.49 in [37.85 mm]
Mounting Mast Diameter	1.57 to 1.97 in [39.88 to 50.04 mm]
Weight	1.1 lbs [498.95 g]

**Environmental Specifications**

<b>Temperature</b>	
Operating Range	-40 to +70 deg C
Wind Survivability	150 MPH [241.4 KPH]
Wind Loading	23.5 lbs at 100 MPH 36.2 lbs at 125 MPH
Humidity	5 to 95

**Plotted and Other Data**

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:  
[617 to 960 MHz + 1710 to 2700 MHz Log Periodic Antenna, 10 to 11 dBi, Dual Band, High gain, Type N Female Connector, V-pol KP-LP1003](#)

617 to 960 MHz + 1710 to 2700 MHz Log Periodic Antenna, 10 to 11 dBi, Dual Band, High gain, Type N Female Connector, V-pol

**KP-LP1003**



---

**Appendix**

**Electrical Downtilt:** Angle in the antenna's elevation pattern in which the maximum gain occurs.

**Gain:** Antenna's average gain.

**Front to Back Ratio @ 180°±30°:** Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

**Cross-polarization Ratio (dB):** Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [617 to 960 MHz + 1710 to 2700 MHz Log Periodic Antenna, 10 to 11 dBi, Dual Band, High gain, Type N Female Connector, V-pol KP-LP1003](#)

URL: <https://www.kpperformance.com/No-URL-Convention-Found-for-?KP-LP1003-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. KP Performance reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. KP Performance does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and KP Performance does not assume liability arising out of the use of any part or document.

617 to 960 MHz + 1710 to 2700 MHz Log Periodic Antenna, 10 to 11 dBi,  
Dual Band, High gain, Type N Female Connector, V-pol

**KP-LP1003 CAD Drawing**

