

790 to 960 MHz + 1710 to 2170 MHz + 2300 to 2700 MHz Log Periodic Antenna, 11 dBi, High Gain, Multi Band, Type N Female connector, V-pol

KP-LP1006



Features

- Frequency coverage for 790 MHz to 2700 MHz
- Very High Gain 11 dBi Directional Antenna
- Each connector covers wide band of frequencies
- Easy Install universal mounting bracket provided
- Weatherproof ABS radome
- Pigtail – 12 inches
- N-Type Female connector

Applications

- Point-to-point, LPWAN, LoRA, LTE-M, NB-IoT, IoT, M2M applications
- 5G / 4G LTE B1 to B21, B23, B24, B25 / 3G / GSM / AWS / WLAN operation supported
- 5G Bands supported
- DAS (Distributed Antenna Systems)
- IEEE 802.11a / b / g / n / ac / ad / ah / ax Wi-Fi applications
- Public safety, utilities, CCTV and local radio coverage
- Smart cities expansion for coverage and IOT / IIOT

Description

The KP-LP1006 from KP Performance Antennas is a high-performance log periodic antenna specifically designed to aesthetically pleasing design. The KP-LP1006 operate from 790 to 2700 MHz for point-to-point applications, 5G, LTE, CMDA, LoRA, IoT, WIFI, where directivity and coverage are very important. The KP Performance Antennas KP-LP1006 has 11 dBi of gain which is ideal for boosting.

The KP Performance Antennas KP-LP1006 has Vertical polarization, 58 horizontal beamwidth, and 47 vertical beamwidth for point-to-point communication. The included mounting brackets allow for either vertical or horizontal mounting configurations with easy install instructions. Where there is weak coverage and needs to reach further distances, log periodic antennas are best. The directional KP-LP1006 antenna has 1 Type N Female connector on a 12 inches long pigtail.

KP Performance KP-LP1006 log periodic antenna operates in 5G bands n1, n2, n3, n5, n7, n8, n18, n20, n25, n26, n30, n34, n38, n39, n40, n41, n53, n65, n66, n67, n70, n80, n81, n82, n84, n86, n89, n90, n91, n92, n93, n94, n95, n97, n98 with a 11 dBi max. This 790 to 2700 MHz 5G directional log periodic antenna with Type N connector is in stock and ready to ship the same day. Our expert technical support and friendly, knowledgeable customer service personnel are available to assist you with your particular needs for high performance Log Periodic antenna engineered for superior performance antennas.

Configuration

Design	Log Periodic
Band Type	Multi
Radiation Pattern	Directional
Polarization	Vertical
Cable Type	Coax Cable
Cable Length	11.81 in [299.97 mm]
Connector Type	N Female
Number of Ports	1

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	790		2,700	MHz
Input VSWR		1.5:1	1.7:1	
Impedance		50		Ohms

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [790 to 960 MHz + 1710 to 2170 MHz + 2300 to 2700 MHz Log Periodic Antenna, 11 dBi, High Gain, Multi Band, Type N Female connector, V-pol KP-](#)

790 to 960 MHz + 1710 to 2170 MHz + 2300 to 2700 MHz Log Periodic Antenna, 11 dBi, High Gain, Multi Band, Type N Female connector, V-pol



KP-LP1006

Gain	10	11	dBi
Front to Back Ratio	25		dB
Horizontal Beamwidth	51	58	Degrees
Vertical Beamwidth	42	47	Degrees
Input Power		100	Watts

Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	0.79 to 0.96	1.71 to 2.17	2.3 to 2.7			GHz
Gain	10	10.5	11			dBi
Horizontal HPBW	58	55	51			Degrees
Vertical HPBW	47	46	42			Degrees
Front to Back Ratio	25	25	25			dB
VSWR Max	1.7:1	1.5:1	1.5:1			
Maximum Input Power	100	100	100			Watts

Mechanical Specifications

Radome Material	ABS
Size	
Length	17.4 in [441.96 mm]
Width	8.3 in [210.82 mm]
Height	2.5 in [63.5 mm]
Weight	2.2 lbs [997.9 g]

Environmental Specifications

Temperature	
Operating Range	-40 to +65 deg C
Wind Survivability	130.5 MPH [210.02 KPH]
Wind Loading	23.5 lbs at 100 MPH 36.2 lbs at 125 MPH

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[790 to 960 MHz + 1710 to 2170 MHz + 2300 to 2700 MHz Log Periodic Antenna, 11 dBi, High Gain, Multi Band, Type N Female connector, V-pol KP-](#)

790 to 960 MHz + 1710 to 2170 MHz + 2300 to 2700 MHz Log Periodic Antenna, 11 dBi, High Gain, Multi Band, Type N Female connector, V-pol

KP-LP1006



Appendix

Electrical Downtilt: Angle in the antenna's elevation pattern in which the maximum gain occurs.

Gain: Antenna's average gain.

Front to Back Ratio @ 180°±30°: Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

Cross-polarization Ratio (dB): Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [790 to 960 MHz + 1710 to 2170 MHz + 2300 to 2700 MHz Log Periodic Antenna, 11 dBi, High Gain, Multi Band, Type N Female connector, V-pol KP-LP1006](#)

URL: <https://www.kpperformance.com/No-URL-Convention-Found-for-?KP-LP1006-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. KP Performance reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. KP Performance does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and KP Performance does not assume liability arising out of the use of any part or document.

790 to 960 MHz + 1710 to 2170 MHz + 2300 to 2700 MHz Log Periodic Antenna,
 11 dBi, High Gain, Multi Band, Type N Female connector, V-pol

KP-LP1006 CAD Drawing

