

4.9 GHz to 6.4 GHz, 65 Degree Sector
Antenna, 17.5 dBi, 8-Port, ±45 Slant

KPP-5SX8-65

Configuration

Design	Sector
Band Type	Single
Radiation Pattern	Directional
Polarization	45 Deg. Slant
Connector Type	N Female
Interface 2	N Female
Number of Ports	8

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	4,900		6,400	MHz
Input VSWR			1.7:1	
Impedance		50		Ohms
Gain		17.5		dBi
Front to Back Ratio	40			dB
Electrical Downtilt		0		Degrees
Cross Polarization Ratio	15			dB
Horizontal (Azimuth) HPBW		60		Degrees
Vertical (Elevation) HPBW		8		Degrees
Input Power			50	Watts

Electrical Specification Notes:
Max input power is 50W per port.

Mechanical Specifications

Radome Material	UV Resistant PVC
Housing Material	Anodized Aluminum
Size	
Length	28.8 in [731.52 mm]
Width	8.7 in [220.98 mm]
Height	2.6 in [66.04 mm]
Mounting Mast Diameter	0.75 to 4.5 in [19.05 to 114.30 mm]
Weight	18 lbs [8.16 kg]

Mechanical Specification Notes:
Anodized aluminum back reflector, aluminum brackets, UV-resistance radome, and hoisting hook.

Environmental Specifications

Temperature	
Operating Range	-40 to +60 deg C

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications:
[4.9 GHz to 6.4 GHz, 65 Degree Sector Antenna, 17.5 dBi, 8-Port, ±45 Slant KPP-5SX8-65](#)

4.9 GHz to 6.4 GHz, 65 Degree Sector Antenna, 17.5 dBi, 8-Port, ±45 Slant

KPP-5SX8-65

Wind Survivability
Wind Loading

100 MPH [160.93 KPH]

Plotted and Other Data

Notes:

Appendix

Electrical Downtilt: Angle in the antenna's elevation pattern in which the maximum gain occurs.

Gain: Antenna's average gain.

Front to Back Ratio @ 180°±30°: Average difference between the antenna's maximum gain and the maximum gain in the antenna's back lobe over ±30° angles.

Cross-polarization Ratio (dB): Typical difference between the co-polarization and cross-polarization gain across the sector's 3 dB Beam Width.

Dedicated to serving the needs of the Wireless Internet Service Provider (WISP) market, KP Performance Antennas offers purpose built products that reliably perform in the field. KP Performance Antennas product line consists of Yagi, Grid, Omni, Dish and other style antennas that operate in the 900 MHz, 2.4 GHz, 3 GHz, and 5 GHz frequencies.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [4.9 GHz to 6.4 GHz, 65 Degree Sector Antenna, 17.5 dBi, 8-Port, ±45 Slant KPP-5SX8-65](#)

URL: <https://www.kpperformance.com/4.9ghz-6.4ghz-65degree-sector-antenna-17.5dbi-8-port-45-slant-kpp-5sx8-65-p.aspx>

The information contained within this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part in order to implement improvements. KP Performance reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. KP Performance does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and KP Performance does not assume liability arising out of the use of any part or document.

KPP-5SX8-65 CAD Drawing

